



**Key Features :**

- Day and night vision weatherproof IR camera .
- Φ5:24pcs IR Led.
- IR Effective Viewing Distance: 25M.
- Built-in 3.6mm / 6mm / 8mm Fix Lens.
- Minimum illumination of 0.00 Lux (led on).
- IP66 Weatherproof standard.
- Auto Tracking White Balance.
- Cable Hidden Design.
- Double Glass + Hoop Unique Design
- Housing Diameter : 60 mm

**Specification**

Model No. :	WIS-TSH-012	WIS-TST-012	WIS-TSU-012	WIS-TSM-012	WIS-TSD-012	WIS-FSD-012	WIS-TPD-012	WIS-FPD-012	
System	PAL / NTSC								
Image Sensor(CCD)	1/3" SONY EFFIO-E	1/3" Ex-View Sony				1/4" Sony	1/3" Sharp	1/4" Sharp	
Picture Elements	PAL: 752(H) x 582(V) / NTSC: 768(H) x 494(V)					PAL: 500(H) x 582(V) / NTSC: 510(H) x 492(V)			
Video output	1.0Vp-p, 75II Composite, BNC x 1								
Horizontal resolution	700TVL	600TVL	520TVL	480TVL	420TVL				
S/N Ratio	≥48dB								
illumination	0.0001 Lux	0.001 Lux	00.1 Lux	00.1 Lux	0.5 Lux	0.8 Lux			
IR LED	Φ5:24pcs IR leds								
illumination	0.000 Lux								
Electronic Shutter	1/50 - 1/10,000S								
White Balance	Auto								
Gamma Ratio	≥0.45								
Infrared Wavelength	850nm								
Lens Mount	Built-in 3.6mm/6mm/8mm Fix Lens								
Temperature	Outdoor: -10C to 50C								
Humidity	0 to 95% RH (non-condensing)								
Sync system	2:1 interlace internal Sync.								
Power supply	12V DC								
	300mA	300mA	300mA	350mA	300mA	300mA	250mA		
Weight	Appro x 0.65kg								
Manufacturer	JBE CCTV								

\* The Specification maybe changed without notice !